



China abec 9 Bearing Supplier



6212 6213 6214 6215- O&Kai Z1V1 Z2V2 Z3V3
ISO Deep Groove Ball Bearing SKF NSK NTN
NACHI Koyo OEM

Bearing No. 6212

6212 Bearing 2D drawings and 3D CAD models

Size	60x110x22 mm
Bore Diameter	60 mm
Outer Diameter	110 mm
Width	22 mm
d	60 mm
D	110 mm
B	22 mm
C	22 mm
r min.	1.5 mm
da min.	69 mm
Da max.	101 mm
ra max.	1.5 mm
Weight	0.783 Kg
Basic dynamic load rating (C)	52,5 kN
Basic static load rating (C0)	36 kN
(Grease) Lubrication Speed	5800 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0



China abec 9 Bearing Supplier

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nachiamerica.com
Outer Race Width	0.866 Inch 22 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	2.362 Inch 60 Millimeter
Outside Diameter	4.331 Inch 110 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	60 mm
Width	22 mm
Fillet Radius/Chamfer	1.5 mm
Dynamic Load Rating	52,500 N



China abec 9 Bearing Supplier

Static Load Rating	36,000 N
Limiting Speed - Grease	6,000 rpm
Limiting Speed - Oil	7,100 rpm
Factor fo	14.3
Radial Clearance	0.008 to 0.028 mm
da (min)	69 mm
Da (max)	101 mm
ra (max)	1.5 mm